## **Sprint stretcher**

The Sprint stretcher allows treatment of patient easily and quickly. The diagnostics is facilitated by possibility of X-ray examination directly on the stretcher.



### X-RAY EXAMINATION

- Thanks to the possibility of X-ray scanning on the stretcher the time necessary for diagnostics is reduced. Seriously injured patient cannot be easily transferred to X-ray table.
- Sprint in version for X-ray examination is equipped with X-ray cassette holder that can be slid under the entire mattress platform.
- Mattress platform is made from the material that is translucent for X-rays.
- X-ray cassette holder can be slid out at both ends of the stretcher without tilting the bac-

### RANGE OF EXAMINATION

- The X-ray photography by the help of transportable X-ray device is possible to use the whole length of mattress platform thanks to the holder of X-ray cassette. This way is possible to sciagraph also the head of the patient.
- During the C-arm diagnostics is the patient's body accessible from the neck to a lower part of legs.



Thanks to the holder it is possible to attach the cassette to backrest.



mattress platform.



Lengthwise gauges on the stretcher frame make the positioning of the cassette easier.

Column construction of the undercarriage facilitates the handling with C-arm.



Possibility of X-ray scanning directly on the stretcher accelerates the diagnostics.

### C-ARM DIAGNOSTICS

- The C-arm can be used for various examination procedures on Emergency, e.g. inserting temporary intra-cardial stimulation or catheterizati-
- Thanks to a translucent mattress platform is possible to examine the patient without further manipulation.
- Column frame of the undercarriage and wide range of height adjustment make the handling with C-arm easier.

## **Sprint stretcher**

### BASIC CONFIGURATION

- 2-part mattress platform, tiltable backrest 0°-70°.
- Adjustable height of mattress platform.
- Collapsible siderails with plastic handrail.
- 4 castors with a 200 mm diameter, centrally operated.
- Equipotentially bonded.
- Protective corner bumpers and plastic bars around the whole perimeter.
- TR/ATR.. tilting, indicator of the tilt.
- Integrated horizontal oxygen bottle holder with securing belt.
- Stacking space on undercarriage.
- 4 holders for infusion rod, 4 for other accessories, 4 holders for drainage bags, holders for restraining belts.

### **OPTIONS**

configuration

- 5th castor, lockable in a directional position for easier stretcher handling.
- Retractable handrail placed at the foot and/or head end of the stretcher.
- Foldable telescopic infusion rod with two hooks (can be placed in every corner of the stretcher).
- Standardized stainless-steel rails which can be attached under both ends of the stretcher.



Using the 5th castor makes the handling with Sprint

MODELS

Sprint Transport

Sprint for C-arm scanning

Mattress platform is translucent for X-rays

Sprint for C-arm scanning and X-ray pho-

Mattress platform is translucent for X-rays.

Stretcher is equipped with holder of X-ray

scopi<mark>c infusion rod is possibl</mark>e to fold under the level of the mattress platform.

### MATTRESS

attre

## There are three types of special mattress designed for the Sprint stretcher. The materials used meet the requirements for durability and easy cleaning.

Sprint Standard

Thickness 6 cm. Antistatic cover is waterproof and washable, zipper is covered. Mattress core is made from HR foam with reduced flammability.

Sprint Plus

Thickness 6 cm. Antistatic cover is waterproof and washable. Mattress contains special slide-out mats for easier patient transfer. Mattress core is made from HR foam with reduced flammability.

Sprint Comfort

Thickness 10 cm. Antistatic cover is waterproof and washable. Core is made from combination of visco-elastic and HR foam with reduced flammability. Thickness of the mattress brings more comfort to the patient.



Mattress Sprint Plus contains special plastic mats for facilitating the transfer of the patient.

### TECHNICAL PARAMETERS

TEOTH VIONET / NO WIETERO	
Outer dimensions	$75,5 \times 205 \text{ cm}$
Mattress platform	65 x 192 cm
Siderails height	
above mattress platform	40 cm
Siderails length	140 cm
Mattress platform	
height adjustment	58,5 - 90,5  cm
Backrest tilt	0° - 70°
TR/ATR tilt	12°/12°
Castors diameter	200 mm
Safe working load (SWL)	230 kg






## SPRINT

## universal transport stretcher











- Unique mattress
- Easy transport

Mattress platform

Adjustment of the backrest

in a range 0° - 70°.

 Undercarriage cover is designed for storage

of equipment and oxygen

bottle (2, 5, 10 litres).

Castor brakes

Foot controls

platform.

central locking system with accessibility from every

corner of the stretcher.

used by nursing staff for heigh

adjustment and tilting of mattress

X-ray examination on the stretcher

The universal transport stretcher Sprint is intended for prompt and safe transport of the patient. Sprint provides the possibility to perform a diagnosis and treatment of the patient with a critical health condition directly on the stretcher. This designate Sprint to the severe conditions during the urgent admission of patients. The design of Sprint was developed with reference to ergonomics and functionality. The parameters and equipment of the stretcher result from the requirements of clinical practice.

Mattress

Fifth castor

makes manipulation

with the stretcher easier

is transparent for X-rays. Cover

is made from antistatic, washable

### WHERE SPRINT IS USED

- The Sprint stretcher is especially designed for the transport of patients in a critical health state. The Sprint fulfils the demands for the treatment and transport of patients in Emergency wards.
- Sprint is suitable to use for the common transport of patients between hospital wards.
- It is possible to use the stretcher as an operating table for one day surgery, for less serious treatment procedures and for post operative recovery.

Collapsible siderails

ergonomical grip

Retractable handrail

of the stretcher.

Hydraulic lifting units

to TR / ATR position.

are placed in telescopic

columns, enabling easy and fast

height adjustment and tilting

handrail is possible to place

in head and / or foot end

do not exceed outline

of the stretcher in any position.

with sturdy handrails for





Foot controls are placed on both sides of the

## **EASY CONTROL**

- All control parts of the stretcher are easy to access and allow unlimited control of all the
- Backrest tilting is easier thanks to the use of
- The adjustment of height and tilting of the mattress platform is operated by foot controls, which are accessible from both sides of the
- The large construction of the foot controls is resistant, even under frequent strain, to dam-

Robust parts protect the stretcher in the extreme conditions of urgent admission.

Column construction and undercarriage cover

make cleaning easier.

### **DURABLE FRAME**

- The Sprint stretcher has been developed with an emphasis on the high operating stress which is usual for healthcare equipment in an Emergency background.
- Siderails and control handrails are covered by sturdy plastic profiles.
- The complete perimeter of the stretcher is equipped with protective plastic bars. The corners are equipped with corner bumpers.
- The stretcher frame forms a stable enough base even for the resuscitation of patients.

### QUICK CLEANING

- All surfaces of the stretcher are designed for easy cleaning, with a minimum area of possible contamination.
- Smooth and compact surface of the lifting columns is easy to clean.
- The undercarriage of the stretcher is protected from contamination by a plastic cover.
- Mattresses used with the Sprint stretcher are equipped with an antistatic and water-





The preconditions of the guick transport of a patient are good driving properties and easy maneuverability of the stretcher. The safe transfer of a patient from or onto the stretcher is also an important feature.

hazardous and difficult for nursing staff.

a unique mattress, Sprint Plus, which con-

tains rigid pullout mats. These mats create a

firm area for transferring the patient from the

stretcher to the bed or onto the operating ta-

The transfer of patient with the help of slide-

out pads is safer and more comfortable and

decreases the strain on nursing staff.

## QUICK TRANSPORT

- The undercarriage of the stretcher is designed to be stable in any situation.
- Four castors with diameter 200 mm increase the undercarriage clearance so the stretcher can be used on rough surfaces.
- The fifth castor sets the direction of riding and allows Sprint to be turned on the spot. Therefore the stretcher can be turned in a smaller area, which is important in narrow corridors and turnings. The force that is needed to turn the stretcher is 5 times lower when there is a directional fifth castor.

The range of accessories of the stretcher

SPRINT enable the parameters of the stret-

cher to conform to specific requirements in

Vertical holder for 5L oxygen bottle

Simple infusion stand with two hooks

various hospital wards.

Simple riding handrails

Monitor tray

Restraint belts






# The repeated transfer of a patient is always The Sprint stretcher can be equipped with

Excellent driving properties of the Sprint ensure

Pair of handrails for easier handling with the



Simple infusion stand is possible to place in every corner of the stretcher.

The stable tray can be used for placing the monitor or the other medical appliances.



used as a foot end of the stretcher.



Vertical oxygen bottle holder is possible to hang on the corner of the stretcher.